


P.V.D.F 4 COATING

CHARACTERISTICS AND USAGE

4 Coat 4 Bake PVDF resin provide 20 years anti-weather performance and surface condition.

- High-weather resistance and chemical resistance obtained through the outstanding molecular bond strength of poly vinylidene fluoride. High-quality prepainted special steel sheets with a 20 years warranty.
- Used for, Skyscraper, Certain purpose building etc.

SECTION OF PAINTED PRODUCT



HANDLING DESCRIPTION

1 During transportation

- At the process of transportation, pls. attach the rubber pad on the skid to avoid the block ing problem.
And pls, cover the coil to protect from rain or snow that might cause from white rust.

2 Storage & handling

- The coil must be kept in the warehouse pls. Handle it with care. And pls, do not pile up more than two stories.

3 Using

- If some part of surface is contaminated, pls. wash it away with a solvent.
And if any peel-off, you should follow the instruction that we would give.

4 Long term storage

- This should be used (roll formed or fabricated) within 6 months from shipping date.
It may take place the zinc peel-off because of aging effect.

5 Application use

- All forming, cutting, transportation storage, and installation of the roofing sheets or panels should be carried out in accordance with good standards of practice, and in particular any storage of the product at a building site should not exceed one month, during which time the product should be kept dry and away from sources of wet or moisture.
- Forming, fabricating and all processing should be carried out in such a way that does not cause cracks or scratches in the coatings.

6 Beware moisture

- They should be protected from moisture which can cause white rust or rust.