


SPECIAL PRODUCTS

SUNCOOL


CHARACTERISTICS AND USAGE

SUNCOOL is environmental friendly and functional Pre-paint steel with ability of infrared rays reflection and brings reduction of air conditioning cost.

- Cutting down the energy cost by the air conditioning
: Around 4% Energy efficiency will be improved by high heat reflection ratio.
- The comparison of the reflection and temperature of SUNCOOL.



SECTION OF PAINTED PRODUCT



Note 1) Materials used for prepainted steel sheet: GI, SGL, AL, SUS etc.

Note 2) 2COAT 2BAKING is available for coating layer on both the top and back sides.

Note 3) Standard 20+30 μ m

HANDLING DESCRIPTION

1 During transportation

- At the process of transportation, pls. attach the rubber pad on the skid to avoid the block ing problem. And pls, cover the coil to protect from rain or snow that might cause from white rust.

2 Storage & handling

- The coil must be kept in the warehouse pls. Handle it with care. And pls, do not pile up more than two stories.

3 Using

- If some part of surface is contaminated, pls. wash it away with a solvent. And if any peel-off, you should follow the instruction that we would give.

4 Long term storage

- This should be used (roll formed or fabricated) within 6 months from shipping date. It may take place the zinc peel-off because of aging effect.

5 Application use

- All forming, cutting, transportation storage, and installation of the roofing sheets or panels should be carried out in accordance with good standards of practice, and in particular any storage of the product at a building site should not exceed one month, during which time the product should be kept dry and away from sources of wet or moisture.
- Forming, fabricating and all processing should be carried out in such a way that does not cause cracks or scratches in the coatings.

6 Beware moisture

- They should be protected from moisture which can cause white rust or rust.